

The LifeSize Icon Series is a line of video systems designed around your experience. Accelerate effective, face-to-face business discussions with your customers, partners, suppliers and colleagues. Access the powerful video applications of the LifeSize® UVC Platform™ through the radically simplified user experience of the LifeSize Icon Series. Representing the culmination of years of innovation and purposeful design, the LifeSize Icon Series delivers the smart video™ experience—frustration-free video conferencing at an unbeatable value so you can focus on what matters the most—your business.

Your Radically Simplified Video Experience

LifeSize Icon systems are designed for a radically simplified user experience. Always know your schedule of video calls. Get helpful reminders if you're running late for a video conference. Easily find and join conference calls with many people. Quickly search for and find business contacts to collaborate with over video. Record and stream important discussions. All these capabilities and more are easily available to you via the new user experience. And if you need more capabilities down the road, simply contact your IT support team to enable the features and applications you need. We have designed the LifeSize Icon Series for maximum simplicity, flexibility and value.

Seeing Is Believing

- The radically simplified user experience means it's fast and easy to collaborate since screen options logically follow what you want to do over video. See only the video functions available to you and discover the endless possibilities of additional applications without any training needed.
- Your personalized meeting schedule appears on the home screen so you can just walk in and start a call with the click of a button.
- > Convenient meeting reminders pop up so you never have to miss an important video conference again.
- An integrated meeting listing lets you quickly search and join a large meeting. Never dial a complex bridge number again—simply find your desired meeting and click to join over video.
- A unified directory for name-based dialing, search functionality and the ability to pin contacts as favorites all provide you quick and easy access to video calls.
- > Enjoy the same user experience in and out of multiparty conference calls. With the unified user experience, there are no frustrating changes in the experience—no more overlapping menus of options or complicated commands to change views.
- > Easily record presentations and meetings and stream live to any number of viewers with the push of a button.*

Integrated with the LifeSize® UVC Platform™

The LifeSize Icon Series system lets you experience the benefits of powerful, integrated infrastructure applications powered by the LifeSize UVC Platform**. Simplified setup and provisioning allows IT teams to turn on streaming and recording capabilities, manage the network, securely traverse NAT/firewalls, support multiparty video calls and enable new video functionality quickly as your needs change.

Expandable and Flexible

LifeSize delivers extraordinary price/performance leadership in the LifeSize Icon Series. We designed this series to adapt to your changing business needs, which is why we offer the ability to upgrade software and accessories at any time. Whether you'd like to expand your environment with multiple displays, upgrade your performance or add new functionality, LifeSize Icon Series offers investment protection to future-proof your growing business.

Highest Performance, Most Powerful Experience

Enjoy the most advanced, highest performing HD video conferencing experience available. HD 1080p60 video support provides ultimate clarity and fluid motion, while the 1080p presentation capability showcases unmatched detail for promoting collaboration.

At-a-Glance

Streamlined Intuitive UI	Calendar integration, meeting directory, unified user interface during multiparty calls, unified directory, name-based dialing, search and favorites
Integrated with UVC Platform**	Easily add powerful video capabilities by turning on UVC applications. Capabilities include streaming and recording of video calls*, managing the network, securely traversing NAT/ firewalls and hosting multiparty calls
Remote Control	Sleek, new design for quick and easy navigation by any user
Video Quality	Up to 1080p60
Presentation Quality & Sharing	Up to 1080p; physical data port
HD Monitors	Connect up to two displays
HD Camera	Pan, tilt and zoom camera options, including support for up to 1080p60 HD and 10x zoom capability
Digital MicPod	360° triple microphone beam- forming technology for superior voice pickup
Phone*	Touch screen powering both audio and video
Place Anywhere	Mountable option for wall (VESA) or display

^{*} This represents LifeSize's current view of its product development cycle and future directions. It is intended for informational purposes only and should not be interpreted as a commitment on the part of LifeSize makes no warranties, express or implied, for these features.



 $[\]ensuremath{^{**}}$ Requires LifeSize UVC Platform, available as virtualized machine software or hardware.

System Components

LifeSize Icon 600 video system LifeSize Camera 10x or LifeSize Camera 200 LifeSize Digital MicPod or LifeSize Phone, 2nd Generation*

Remote control Power supply/cables

Communications

SIP, H.323, 128 Kbps-6.0 Mbps 1xRJ-45 Network LAN 1x LifeSize Link for 2x LifeSize Digital MicPod or LifeSize Phone, 2nd Generation*

Support for Up to Two Displays

Any 720p or 1080p HD displays supporting HDMI input

HD 1080p60 PTZ Camera (LifeSize Camera 10x)

Wide-angle zoom lens with 70-degree field of view Up to 10x optical zoom

Auto focus/automatic gain control 10 camera presets (near or far end) Standard 3.0 M HDMI cable

HD 1080p30 PTZ Camera (LifeSize Camera 200)

Wide-angle zoom lens with 70-degree field of view Up to 4x optical zoom

Auto focus/automatic gain control 10 camera presets (near or far end) Standard 3.0 M HDMI cable

Video Specifications

Maximum resolution 1920x1080, 16:9 aspect ratio All resolutions progressive scanning up to 60 frames per second

Over 200 resolutions supported

Example bitrates and resolutions (H.264, AAC-LC):

768 Kbps (720p30)

1.1 Mbps (720p60)

1.7 Mbps (1080p30)

2.5 Mbps (1080p60)

Video Standards

H.264, H.263+ and H.239/BFCP

Video Inputs (2 Inputs)

1 x HD Video In (up to 1080p60)

1 x DVI-I In (up to 1080p60)—HDMI/VGA enabled

Video Outputs (2 Outputs)

1 x HD Video Out (up to 1080p60)—Primary display 1 x DVI-I Out (up to 1080p60) HDMI/VGA enabled— Secondary display

Fully Integrated, HD Audio Digital MicPod

90 Hz up to 24 kHz, up to 15 ft pickup range Powered by connected video system directly through LifeSize Link cable

Support for up to two LifeSize Digital MicPods

Fully Integrated, **HD Audio Conference Phone***

90 Hz up to 22 kHz, up to 15 ft pickup range Powered by connected video device directly through LifeSize Link cable

Touch-screen user interface Manage HD video, audio and presentation Additional support for up to two LifeSize Digital

Audio Features

WebRTC NetEQ packet loss concealment Full duplex for natural conversations Echo cancellation for echo-free calls Automatic gain control Automatic noise reduction

Audio Standards

G.711, G.722, G.722.1 and G.722.1C licensed from Polycom®, MPEG-4-AAC-LC

Audio Inputs (4 Inputs)

1 x Mic/Line In (3.5mm) 1 x LifeSize Link (LifeSize Digital MicPod or LifeSize Phone, 2nd Generation*)

1 x HD Video In

1 x DVI-I In

Audio Outputs (4 Outputs)

1 x Line Out/Headset 1 x LifeSize Link (LifeSize Phone, 2nd Generation*)

1 x HD Video Out

1 x DVI-I Out

Other Supported Standards

H.221, H.224, H.225, H.231, H.241, H.242, H.245, H.281, RFC 3261, RFC 3264, RFC 2190, RFC 3407, RFC 2833

User Interface & Features

Simplified user interface

Heads up remote control

Graphical user interface administration console

Multiple languages supported

Do Not Disturb mode

Video mute

Picture-in-Picture

UVC Applications**

Calendar, meeting directory, favorites, unified directory

Record/stream a call, auto-record* all calls, single-button ad-hoc recording, recording indicator

Management of network

Securely traverse NAT/firewalls

Microsoft® Lync™ interop*

Security

Ability to disable HTTP, SSH and Telnet services H.235 (AES) encryption support including strict TLS/SRTP support

Kensington Security Slot

Intelligent Networking Features

Adaptive motion control (AMC) including forward error correction (FEC) for superior video quality in all network conditions

NAT/firewall traversal (H.460/SIP) Auto bandwidth detection

Directory and Address Book

Up to 100,000 directory entries LDAP support/H.350 compliant Calendar/meeting directory support H.323 URI dialing support (Annex O)

System Management

Web interface Backup and restore capability 2x USB 3.0

Power

AC voltage 100-240V, 50-60 Hz, 2.5A via external

Environmental Data

Operating temperature: 0°C (32°F) to 40°C (104°F) Operating humidity: 15% to 85%, noncondensing Storage temperature: -20°C (-4°F) to 60°C (140°F) Storage humidity: 10% to 90%, noncondensing

Video Device Dimensions

Width: 200 mm (7.87") Depth: 150 mm (5.90") Height: 41.3 mm (1.63") Weight: 1.10 Kg (2.42 lbs)

Mounting Options

Mounting holes: 2 x M5 screw holes 307 mm (12 in)

Mounting screws: 2 x M5 screws (Max length: 9 mm, Min length: 4 mm)

- * This represents LifeSize's current view of its product development cycle and future directions. It is intended for informational purposes only and should not be interpreted as a commitment on the part of LifeSize. LifeSize makes no warranties, express or implied, for these features.
- ** Requires LifeSize UVC Platform, available as virtualized machine software or hardware
- *** LifeSize UVC Manager™ included with purchase of LifeSize Icon Series connected video device.





Headquarters

Austin, Texas, USA +1 512 347 9300 Toll Free US +1 877 543 3749

EMEA Regional Office

Munich Germany +49 89 20 70 76 0 Toll Free Europe +00 8000 999 09 799

www.lifesize.com E-mail info@lifesize.com

APAC Regional Office Singapore +65 6303 8370



Delivering the Ultimate Communication Experience

© 2013 Logitech. All rights reserved. Information contained in this document is subject to change without notice. LifeSize is the registered trademark or trademark of Logitech. All other trademarks are the property of their respective owners.

DS Icon EN 0113







